

OUR GLOBAL
COMPETENCE
CENTRES

 APOLLO DISPLAY
TECHNOLOGIES



 DISTEC



 DISPLAY
TECHNOLOGY





Datasheet

IF426-00

IF426-00 Interface AA035AE01

ZU-02-426

Version 0.1

27.02.2019

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. All specifications are subject to change without notice.

Table of Contents

1	Revision History	2
2	Absolut Maximum Ratings	3
3	Electrical Specification	3
4	Mechanical Specification	4
5	Connectors	4
5.1	Input Connectors	4
5.2	Output Connectors	5

1 Revision History

Date	Rev.No.	Description	Page
27.02.2019	0.1	First Draft	All

2 Absolut Maximum Ratings

Item	Symbol	Min.	Max	Unit	Note
Supply Voltage	V_{DD}	-0.3	7.0	VDC	
Supply Voltage	V_{BLU}	10.8	13.2	VDC	
Control Voltages	$V_{ON/OFF}, V_{PWM}$		5.25	V	
Storage Temperature	T_{st}	-30	80	°C	
Operating Temperature	T_{op}	-20	70	°C	

3 Electrical Specification

LVDS

Item	Symbol	Min.	Typ.	Max	Unit	Note
Supply Voltage	V_{DD}	4.75	5.0	5.25	VDC	
Current	I_{DD}		120	160	mA	
Input Power	P_{DD}		0.6	0.84	W	

BLU

Item	Symbol	Min.	Typ.	Max	Unit	Note
Source Voltage	V_{BLU}	11.5	12V	12.5	V	
Source Current	I_{BLU}		0.06		A	LED 3CH
Source Power	P_{BLU}		0.72		W	
Efficiency			88		%	
PWM dimming	PWM	100Hz	180Hz	1000Hz	f	
PWM duty cycle	PWM_{duty}	0.3%		100%	%	2
Min. On Level voltage	$V_{ON/OFF}, V_{PWM}$	2.4		5.0	V	1
Max. Off Level voltage	$V_{ON/OFF}, V_{PWM}$	-0.3		0.8	V	1


Note(1) PWM Mode

Note(2) PWM Duty min depends on PWM frequency

Fpwm(Hz)	Dmin(%)	Dmax(%)
100<F≤200	0.30	100
200<F≤500	0.75	100
500<F≤1K	1.50	100
1K<F≤2K	3.00	100
2K<F≤5K	7.50	100
5K<F≤10K	15.00	100
10K<F≤13K	19.00	100
13K<F≤20K	30.00	100

4 Mechanical Specification

Item	Description	Note
Length	80 mm	± 0.2mm
Width	47 mm	± 0.2 mm
Height (top side)	3.8mm	± 0.2 mm(L1)
Height (PCB)	1.6mm	± 0.1 mm
Height (Bottom)	0	No Components On Bottom Side



5 Connectors

CON	Description	Type	Manufacturer
CN1	Input LVDS Connector	FI-X30SSLA-HF	JAE
CN2	Input Backlight connector	53261-0671	Molex
CN3	Output LVDS Connector	05002HR-H30J05	Yeonho
CN4	Output Backlight Connector	05003HR-H06E D	Yeonho

5.1 Input Connectors

CN1 LVDS input connector

Pin	Signal	Description	Pin	Signal	Description
1	NC	Not Connected	16	R0-	
2	GND	Ground	17	GND	Ground
3	R3+		18	STBYB	
4	R3-		19	NC	Not Connected
5	GND	Ground	20	NC	Not Connected
6	R2+		21	NC	Not Connected
7	R2-		22	NC	Not Connected
8	GND	Ground	23	NC	Not Connected
9	RCLK+		24	NC	Not Connected
10	RCLK-		25	V _{DD}	
11	GND	Ground	26	V _{DD}	
12	R1+		27	GND	Ground
13	R1-		28	NC	Not Connected
14	GND	Ground	29	NC	Not Connected
15	R0+		30	NC	Not Connected

CN2 BLU input connector

Pin	Signal	Description
1	V _{BLU}	BLU Supply Voltage
2	V _{BLU}	BLU Supply Voltage
3	GND	Ground
4	GND	Ground
5	ON/OFF	BLU On/Off
6	PWM	BLU PWM

CN5 SPI input connector

Pin	Signal	Description
1	RSTB	Reset (H:Normal, L:Reset)
2	SCL	SPI Clock
3	SDA	SPI Data (I/O)
4	CSB	SPI Chip Select

5.2 Output Connectors

CN3 LVDS output connector

Pin	Signal	Description	Pin	Signal	Description
1	GND	Ground	16	Link0+	LVDS Link0
2	CSB	SPI Chip Select	17	Link0-	LVDS Link0
3	SDA	SPI Data (I/O)	18	GND	Ground
4	GND	Ground	19	CLKIN+	LVDS Clock
5	SCL	SPI Clock	20	CLKIN-	LVDS Clock
6	GND	Ground	21	GND	Ground
7	Link3+	LVDS Link3	22	STBYB	Stand-by Control (H:Normal, L:Standby)
8	Link3-	LVDS Link3	23	RSTB	Reset (H:Normal, L:Reset)
9	GND	Ground	24	GND	Ground
10	Link2+	LVDS Link2	25	GND	Ground
11	Link2-	LVDS Link2	26	V _{DD}	Digital Power Supply 2.5 V
12	GND	Ground	27	V _{DD}	Digital Power Supply 2.5 V
13	Link1+	LVDS Link1	28	V _{CC}	Analog Power Supply 3.2V
14	Link1-	LVDS Link1	29	V _{CC}	Analog Power Supply 3.2V
15	GND	Ground	30	V _{CC}	Analog Power Supply 3.2V

CN4 BLU output connector

Pin	Signal	Description
1	LED CA1	LED cathode 1
2	LED AN1	LED anode 1
3	LED AN2	LED anode 2
4	LED CA2	LED cathode 2
5	LED CA3	LED cathode 3
6	LED AN3	LED anode 3

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, the UK and the USA. For more information please contact:

Headquarters

Germany



FORTEC Elektronik AG

Lechwiesenstr. 9
86899 Landsberg am Lech

Phone: +49 8191 91172-0
E-Mail: sales@forteca.de
Internet: www.forteca.de

Fortec Group Members

Austria



FORTEC Elektronik AG

Office Vienna
Nuschinggasse 12
1230 Wien

Phone: +43 1 8673492-0
E-Mail: office@fortec.at
Internet: www.fortec.at

Germany



Distec GmbH

Augsburger Str. 2b
82110 Germering

Phone: +49 89 894363-0
E-Mail: info@distec.de
Internet: www.distec.de

Switzerland



ALTRAC AG

Bahnhofstraße 3
5436 Würenlos

Phone: +41 44 7446111
E-Mail: info@altrac.ch
Internet: www.altrac.ch

United Kingdom



Display Technology Ltd.

Osprey House, 1 Osprey Court
Hichingbrooke Business Park
Huntingdon, Cambridgeshire, PE29 6FN

Phone: +44 1480 411600
E-Mail: info@displaytechnology.co.uk
Internet: www.displaytechnology.co.uk

USA



Apollo Display Technologies, Corp.

87 Raynor Avenue,
Unit 1 Ronkonkoma,
NY 11779

Phone: +1 631 5804360
E-Mail: info@apolloDisplays.com
Internet: www.apolloDisplays.com